

## Three Way Male Outlet - Roof Connections

26-295 / 26-297

Used to create roof connections, or fire pump test connections. Provides 250 GPM minimum per outlet.

- material: cast brass

### back outlet

26-295


Pipe Size	(3) Outlets Male	Part #	Powhatan Part #	Wt. Lbs.
4"	2½" NPT	<b>FR3C4025</b>	26-295-00001	12
6"	2½" NPT	<b>FR3C6025</b>	26-295-00005	24
	2½" NH (NST)	<b>FR3C6025F</b>	26-295-00014	24



back outlet connection  
26-295

#### Dimensions

Size	A	B	C
4 x 2½ x 2½ x 2½	12-3/4"	8-3/4"	5-1/4"
6 x 2½ x 2½ x 2½	15-3/8"	9-3/4"	7-5/8"



### bottom outlet

26-297

Pipe Size	(3) Outlets Male	Part #	Powhatan Part #	Wt. Lbs.
4"	2½" NPT	<b>90FR3C4025</b>	26-297-00001	23.25
	2½" NH (NST)	<b>90FR3C4025F</b>	26-297-00014	23.25
6"	2½" NPT	<b>90FR3C6025</b>	26-297-00005	16.25
	2½" NH (NST)	<b>90FR3C6025F</b>	26-297-00006	16.25



bottom outlet connection  
26-297

#### Dimensions

Size	A	B	C	D
4 x 2½ x 2½ x 2½	11-3/4"	7-3/4"	4-7/16"	6-1/4"
6 x 2½ x 2½ x 2½	11-3/4"	7-3/4"	4-7/16"	6-1/4"

